

6800 LEAGUES UNDER THE SEA



NVIDIA®

Deferred Shading

Mark Harris





The Challenge: Real-Time Lighting

- Modern games use many lights on many objects covering many pixels
 - computationally expensive
- Three major options for real-time lighting
 - Single-pass, multi-light
 - Multi-pass, multi-light
 - Deferred Shading
- Each has associated trade-offs



Comparison: Single-Pass Lighting

For Each Object:

Render object, apply all lighting in one shader

- Hidden surfaces can cause wasted shading
- Hard to manage multi-light situations
 - Code generation can result in thousands of combinations for a single template shader
- Hard to integrate with shadows
 - Stencil = No Go
 - Shadow Maps = Easy to overflow VRAM



NVIDIA.



Comparison: Multipass Lighting

For Each Light:

For Each Object Affected By Light:

```
framebuffer += brdf( object, light )
```

- Hidden surfaces can cause wasted shading
- High Batch Count (1/object/light)
 - Even higher if shadow-casting
- Lots of repeated work each pass:
 - Vertex transform & setup
 - Anisotropic filtering



NVIDIA.



Comparison: Deferred Shading

For Each Object:

Render lighting properties to "G-buffer"

For Each Light:

framebuffer += brdf(G-buffer, light)

- Greatly simplifies batching & engine management
- Easily integrates with popular shadow techniques
- "Perfect" $O(1)$ depth complexity for lighting
- Lots of small lights ~ one big light



NVIDIA.



Deferred Shading: Not A New Idea!

- Deferred shading introduced by Michael Deering et al. at SIGGRAPH 1988
 - Their paper does not ever use the word “deferred”
 - PixelFlow used it (UNC / HP project)
- Just now becoming practical for games!





NVIDIA.



What is a G-Buffer?

- **G-Buffer = All necessary per-pixel lighting terms**
 - Normal
 - Position
 - Diffuse / Specular Albedo, other attributes
 - Limits lighting to a small number of parameters!



What You Need



- **Deferred shading is best with high-end GPU features:**
 - **Floating-point textures: must store position**
 - **Multiple Render Targets (MRT): write all G-buffer attributes in a single pass**
 - **Floating-point blending: fast compositing**



NVIDIA.



Attributes Pass

- **Attributes written will depend on your shading**
- **Attributes needed**
 - **Position**
 - **Normal**
 - **Color**
 - **Others: specular/exponent map, emissive, light map, material ID, etc.**
- **Option: trade storage for computation**
 - **Store pos.z and compute xy from z + window.xy**
 - **Store normal.xy and compute $z = \sqrt{1 - x^2 - y^2}$**

MRT rules



- Up to 4 active render targets
- All must have the same number of bits
- You can mix RTs with different number of channels
- For example, this is OK:
 - RT0 = R32f
 - RT1 = G16R16f
 - RT2 = ARGB8
- This won't work:
 - RT0 = G16R16f
 - RT1 = A16R16G16B16f



Example MRT Layout

- Three 16-bit Float MRTs

RT1	Diffuse.r	Diffuse.g	Diffuse.b	Specular
RT0	Position.x	Position.y	Position.z	Emissive
RT2	Normal.x	Normal.y	Normal.z	Free

- 16-bit float is overkill for Diffuse reflectance...
 - But we don't have a choice due to MRT rules



NVIDIA.

Computing Lighting




Render convex bounding geometry

- Spot Light = Cone
- Point Light = Sphere
- Directional Light = Quad or box

Read G-Buffer

Compute radiance

Blend into frame buffer



Courtesy of Shawn Hargreaves,
GDC 2004

- Lots of optimizations possible
 - Clipping, occlusion query, Z-cull, stencil cull, etc.



NVIDIA.



Lighting Details

- Blend contribution from each light into accumulation buffer
 - Keep diffuse and specular separate

For each light:

```
diffuse += diffuse(G-buff.N, L)
specular += G-buff.spec *
             specular(G-buff.N, G-buff.P, L)
```

- A final full-screen pass modulates diffuse color:
`framebuffer = diffuse * G-buff.diffuse + specular`



NVIDIA.



Options for accumulation buffer(s)

- **Precision**

- 16-bit floating point enables HDR
- Can use 8-bit for higher performance
 - Beware of saturation

- **Channels**

- RGBA if monochrome specular is enough
- 2 RGBA buffers if RGB diffuse and specular are both needed.
- Small shader overhead for each RT written




NVIDIA.



Lighting Optimization

- Only want to shade surfaces inside light volume
 - Anything else is wasted work





Optimization: Stencil Cull

- Two pass algorithm, but first pass is very cheap
 - Rendering without color writes = 2x pixels per clock
- 1. Render light volume with color write disabled**
 - Depth Func = LESS, Stencil Func = ALWAYS
 - Stencil Z-FAIL = REPLACE (with value X)
 - Rest of stencil ops set to KEEP
- 2. Render with lighting shader**
 - Depth Func = ALWAYS, Stencil Func = EQUAL, all ops = KEEP, Stencil Ref = X
 - Unlit pixels will be culled because stencil will not match the reference value




NVIDIA.



Setting up Stencil Buffer

- Only regions that fail depth test represent objects within the light volume



Shadows



- **Shadow maps work very well with deferred shading**
 - Work trivially for directional and spot lights
 - Point (omni) lights are trickier...
- **Don't forget to use NVIDIA hardware shadow maps**
 - Render to shadow map at 2x pixels per clock
 - Shadow depth comparison in hardware
 - 4 sample percentage closer filtering in hardware
 - Very fast high-quality shadows!
- **May want to increase shadow bias based on pos.z**
 - If using fp16 for G-buffer positions



NVIDIA.



Virtual Shadow Depth Cube Texture

- **Solution for point light shadows**
 - Technique created by Will Newhall & Gary King
- **Unrolls a shadow cube map into a 2D depth texture**
 - Pixel shader computes ST and depth from XYZ
 - G16R16 cubemap efficiently maps XYZ->ST
 - Free bilinear filtering offsets extra per-pixel work
- **More details in *ShaderX³***
 - Charles River Media, October 2004

Multiple Materials w/ Deferred Shading



- **Deferred shading doesn't scale to multiple materials**
 - Limited number of terms in G-buffer
 - Shader is tied to light source – 1 BRDF to rule them all
- **Options:**
 - Re-render light multiple times, 1 for each BRDF
 - Loses much of deferred shading's benefit
 - Store multiple BRDFs in light shader, choose per-pixel
 - Use that last free channel in G-buffer to store material ID
 - Reasonably coherent dynamic branching
 - Should work well on pixel shader 3.0 hardware



NVIDIA.

Transparency



- **Deferred shading does not support transparency**
 - Only shades nearest surfaces
- **Just draw transparent objects last**
 - Can use depth peeling
 - Blend into final image, sort back-to-front as always
 - Use “normal” shading / lighting
 - Make sure you use the same depth buffer as the rest
- **Also draw particles and other blended effects last**



NVIDIA.



Post-Processing

- **G-buffer + accum buffers can be used as input to many post-process effects**
 - **Glow**
 - **Auto-Exposure**
 - **Distortion**
 - **Edge-smoothing**
 - **Fog**
 - **Whatever else!**
 - **HDR**
- **See HDR talk**

Anti-Aliasing with Deferred Shading




- Deferred shading is incompatible with MSAA
- API doesn't allow antialiased MRTs
 - But this is a small problem...
- AA resolve has to happen after accumulation!
 - Resolve = process of combining multiple samples
- G-Buffer cannot be resolved
 - What happens to an FP16 position when resolved?



NVIDIA.




Shadow Edge, Correct AA Resolve






Shadow Edge, Correct AA Resolve






Shadow Edge, Correct AA Resolve



NVIDIA.




Shadow Edge, Correct AA Resolve



NVIDIA




Shadow Edge, G-Buffer Resolve






Shadow Edge, G-Buffer Resolve





Shadow Edge, G-Buffer Resolve



Other AA options?



- **Supersampling lighting is a costly option**
 - Lighting is typically the bottleneck, pixel shader bound
 - 4x supersampled lighting would be a big perf. Hit
- **“Intelligent Blur” : Only filter object edges**
 - Based on depths and normals of neighboring pixels
 - Set “barrier” high, to avoid interior blurring
 - Full-screen shader, but cheaper than SSAA



NVIDIA.



Should I use Deferred Shading?

- This is an **ESSENTIAL** question
- Deferred shading is not always a win
 - One major title has already scrapped it!
 - Another came close
- Many tradeoffs
 - AA is problematic
 - Some scenes work well, others very poorly
- The benefit will depend on your application
 - Game design
 - Level design



When is Deferred Shading A Win?

- **Not when you have many directional lights**
 - Shading complexity will be $O(R*L)$, R = screen res.
 - Outdoor daytime scenes probably not a good case
- **Better when you have lots of local lights**
 - Ideal case is non-overlapping lights
 - Shading complexity $O(R)$
 - Nighttime scenes with many dynamic lights!
- **In any case, make sure G-Buffer pass is cheap**



NVIDIA.



Gosh, what about z-cull & SM3.0?

- Isn't the goal of z-cull to achieve deferred shading?
 - Do an initial front-to-back-sorted z-only pass.
 - Then you will shade only visible surfaces anyway!
- Shader Model 3.0 allows “uber shaders”
 - Iterate over multiple lights of different types in “traditional” (non-deferred) shading
- Combine these, and performance could be as good (better?) than deferred shading!
 - More tests needed



NVIDIA.

We don't have all the answers



- We can't tell you to use it or not
 - Experimentation and analysis is important
 - Depends on your application
 - Need to have a fallback anyway

Sorry to end it this way, but...



**MORE RESEARCH IS NEEDED!
PLEASE SHARE YOUR FINDINGS!**

(you can bet we'll share ours)

Questions?



- <http://developer.nvidia.com>
- mharris@nvidia.com



NVIDIA.

GeForce 6800 Guidance (1 of 6)



- **Allocate render targets FIRST**
 - Deferred Shading uses many RTs
 - Allocating them first ensures they are in fastest RAM
- **Keep MRT usage to 3 or fewer render targets**
 - Performance cliff at 4 on GeForce 6800
 - Each additional RT adds shader overhead
 - Don't render to all RTs if surface doesn't need them
 - e.g. Sky Dome doesn't need normals or position



NVIDIA.

GeForce 6800 Guidance (2 of 6)



- **Use aniso filtering during G-buffer pass**
 - Will help image quality on parts of image that don't benefit from "edge smoothing AA"
 - Only on textures that need it!
- **Take advantage of early Z- and Stencil culling**
 - Don't switch z-test direction mid-frame
 - Avoid frequent stencil reference / op changes

GeForce 6800 Guidance (3 of 6)



- **Use hardware shadow mapping (“UltraShadow”)**
 - **Use D16 or D24X8 format for shadow maps**
 - **Bind 8-bit color RT, disable color writes on updates**
 - **Use tex2Dproj to get hardware shadow comparison**
 - **Enable bilinear filtering to get 4-sample PCF**

GeForce 6800 Guidance (4 of 6)



- **Use fp16 filtering and blending**
 - **Fp16 textures are fully orthogonal!**
 - **No need to “ping-pong” to accumulate light sources**
- **Use the lowest precision possible**
 - **Lower-precision textures improve cache coherence, reduce bandwidth**
 - **Use half data type in shaders**



NVIDIA.

GeForce 6800 Guidance (5 of 6)



- **Use write masks to tell optimizer sizes of operands**
 - **Can schedule multiple instructions per cycle**
 - Two simultaneous 2-component ops, or
 - One 3-component op + 1 scalar op
- **Without write masks, compiler must be conservative**



NVIDIA.

GeForce 6800 Guidance (6 of 6)



- Use fp16 normalize()
 - Compiles to single-cycle nrmh instruction
 - Only applies to half3, so:

```
half3 n = normalize(tex2D(normalmap, coords).xyz); // fast
half4 n = normalize(tex2D(normalmap, coords));      // slow
float3 n = normalize(tex2D(normalmap, coords).xyz); // slow
```



NVIDIA.



Example Attribute Layout

- Normal: x, y, z
- Position: x, y, z
- Diffuse Reflectance: RGB
- Specular Reflectance (“Gloss Map”, single channel)
- Emissive (single channel)
- One free channel
 - Ideas on this later
 - Your application will dictate



NVIDIA.